

# ROUGH TERRAIN CRANE

## TR-200M

### *JAPANESE SPECIFICATIONS*

OUTLINE	SPEC. NO.
4-section Boom, 1-stage Jib	TR-200M-4-00101

Control No. JA-01

# TR-200M

## CRANE SPECIFICATIONS

### CRANE CAPACITY

8.5m Boom	20,000kg	at 3.5m	( 7 part-line)
14.6m Boom	16,000kg	at 3.5m	( 6 part-line)
20.7m Boom	9,000kg	at 6.0m	( 4 part-line)
26.8m Boom	6,800kg	at 7.0m	( 4 part-line)
7.5m Jib	3,000kg	at 70°	( 1 part-line)
Single top	3,000kg		( 1 part-line)

### MAX. LIFTING HEIGHT

Boom	27.5m
Jib	34.6m

### MAX. WORKING RADIUS

Boom	25.0m
Jib	30.3m

### BOOM LENGTH

8.5m – 26.8m

### BOOM EXTENSION

18.3m

### BOOM EXTENSION SPEED

18.3m / 78s

### JIB LENGTH

7.5m

### MAIN WINCH SINGLE LINE SPEED

High range:	121m/min	(4th layer)
Low range:	58m/min	(4th layer)

### MAIN WINCH HOOK SPEED

High range:	17.3m/min	(7 part-line)
Low range:	8.3m/min	(7 part-line)

### AUXILIARY WINCH SINGLE LINE SPEED

High range:	103m/min	(2nd layer)
Low range:	50m/min	(2nd layer)

### AUXILIARY WINCH HOOK SPEED

High range:	103m/min	(1 part-line)
Low range:	50m/min	(1 part-line)

### BOOM ELEVATION ANGLE

0° – 82°

### BOOM ELEVATION SPEED

0° – 82° / 34s

### SWING ANGLE

360° continue

### SWING SPEED

3.4rpm

### WIRE ROPE

Main Winch

16mm × 150m (Diameter × Length)  
 7×7 + 6×Fi(29) Class B ordinary · Z twist  
 Spin-resistant wire rope  
 Breaking strength 17.6t

Auxiliary Winch

16mm × 80m (Diameter × Length)  
 7×7 + 6×Fi(29) Class B ordinary · Z twist  
 Spin-resistant wire rope  
 Breaking strength 17.6t

### BOOM

4-section hydraulically telescoping boom of box construction.

(stage 2: sequential; stages 3, 4: synchronized)

### BOOM EXTENSION

2 double-acting hydraulic cylinder  
 1 wire rope type telescoping device

### JIB

1-staged swingaround boom extension which stores alongside boom base section.  
 Triple offset (5°, 25°, 45°) type.

### SINGLE TOP

Single sheave. Mounted to main boom head for single line work.

### HOIST

Driven by hydraulic motor and via planetary gear reducer. With free-fall device.

Automatic brake (with foot brake for free-fall device)

2 single winches

### BOOM ELEVATION

1 double-acting hydraulic cylinders

### SWING

Hydraulic motor driven planetary gear reducer

Swing bearing

Swing free/lock changeover type

Hand brake

### OUTRIGGERS

Fully hydraulic X-type (floats mounted integrally)

Slides and jacks each provided with independent operation device.

Full extended width 5.8m

Middle extended width 4.7m

Minimum extended width 3.6m

### MAX. OUTRIGGER LOAD

22.6t

### HYDRAULIC PUMPS

Variable piston pump and gear pump

### HYDRAULIC OIL TANK CAPACITY

375 liters

### SAFETY DEVICES

Automatic moment limiter (AML)

With working range function

Over-winding cutout

Working area control device

Level gauge

Hook safety latch

Winch drum lock

Hydraulic safety valve

Telescopic counterbalance valve

Elevation counterbalance valve

Jack pilot check valve

Swing lock

### EQUIPMENTS

Crane cab heater (with defroster)

Hydraulic oil temperature indication lamp

Oil cooler

Winch drum rotation indicator

Operation pedals for elevating/ telescoping

Jib extending device

Radio

## CARRIER SPECIFICATIONS

### ENGINE

Model MITSUBISHI 6D14  
 Type 4-cycle, 6-cylinder, direct-injection, water-cooled diesel engine (with turbo charger)  
 Piston displacement 6,557cc  
 Max. output 185PS at 2,800rpm  
 Max. torque 58kg·m at 1,600rpm

### TORQUE CONVERTER

3-element, 1-stage unit (with automatic lock-up mechanism)

### TRANSMISSION

Power shift type (wet multi-plate clutch)  
 3 forward and 1 reverse speeds

### REDUCER

Axle dual-ratio reduction

### DRIVE

2-wheel drive (4×2) / 4-wheel drive (4×4) selection

### FRONT AXLE

Full floating type

### REAR AXLE

Full floating type (with no-spin differential)

### SUSPENSION

Front Parallel leaf spring type  
 Rear Parallel leaf spring type

### STEERING

Fully hydraulic power steering  
 With reverse steering correction mechanism

### BRAKE SYSTEM

Service Brake

Hydro-pneumatic brake  
 Disk brake

Parking Brake

Mechanically operated, internal expanding duo-servo shoe type acting on drum at transmission case rear.

Auxiliary Brake

Electro-pneumatic operated exhaust brake.  
 Auxiliary braking device for operations

### FRAME

Welded box-shaped structure

### ELECTRIC SYSTEM

24 V DC. 2 batteries of 12V (120Ah)

### FUEL TANK CAPACITY

250 liters

### TIRES

Front 14.00R24 ☆☆☆(OR)  
 Rear 14.00R24 ☆☆☆(OR)

### CAB

Two-man type

With sun visor and trim  
 Rubber mounted type  
 Fully adjustable seat (with headrest, seat belt)  
 Adjustable handle (tilt, telescoping)  
 Roof windshield lock warning

### SAFETY DEVICES

Emergency steering device  
 Spring lock device  
 Rear wheel steering lock device  
 Engine over-run alarm  
 Overshift prevention device  
 Parking brake alarm

## GENERAL DATA

### DIMENSIONS

Overall length	10,470mm
Overall width	2,490mm
Overall height	3,420mm
Wheel base	3,100mm
Tread Front	2,070mm
Tread Rear	2,070mm

### WEIGHTS

Gross vehicle weight	
Total	23,350kg
Front	11,675kg
Rear	11,675kg

### PERFORMANCE

Max. traveling speed	49km/h
Gradeability (tan θ)	0.6
Min. turning radius	4.7m (4-wheel steering) 8.0m (4-wheel steering)

**TOTAL RATED LOADS**

(1) With outriggers set (360°)

(i)

Unit:ton

Outriggers fully extended.								
A B (m)	8.5m	14.6m	20.7m	26.8m	C D E (°)	7.5m		
						5°	25°	45°
2.5	20.0	16.0	9.0		82	3.0	2.1	1.6
3.0	20.0	16.0	9.0		75	3.0	2.1	1.6
3.5	20.0	16.0	9.0	6.8	70	3.0	2.1	1.6
4.0	18.5	15.5	9.0	6.8	65	2.5	1.9	1.5
4.5	16.5	14.3	9.0	6.8	60	2.1	1.75	1.45
5.0	15.0	13.2	9.0	6.8	55	1.75	1.55	1.35
5.5	13.7	12.2	9.0	6.8	50	1.35	1.25	1.15
6.0	12.5	11.4	9.0	6.8	45	1.05	1.0	0.95
6.5	11.5	10.6	8.5	6.8	40	0.85	0.8	
7.0		9.9	8.1	6.8	35	0.7	0.65	
8.0		8.0	7.3	6.15	30	0.55	0.55	
9.0		6.55	6.5	5.55	25	0.45		
10.0		5.45	5.75	5.05				
11.0		4.6	4.9	4.65				
12.0		3.85	4.25	4.25				
13.0			3.7	3.8				
14.0			3.2	3.35				
15.0			2.75	2.95				
16.0			2.45	2.65				
17.0			2.15	2.35				
18.0			1.9	2.1				
19.0				1.85				
20.0				1.65				
22.0				1.3				
24.0				1.0				
25.0				0.85				

A = Boom length  
 B = Working radius  
 C = Jib length  
 D = Jib offset  
 E = Boom angle

(ii)

Unit:ton

Outriggers middle extended								
A B (m)	8.5m	14.6m	20.7m	26.8m	C D E (°)	7.5m		
						5°	25°	45°
2.5	20.0	16.0	9.0		82	3.0	2.1	1.6
3.0	20.0	16.0	9.0		75	3.0	2.1	1.6
3.5	20.0	16.0	9.0	6.8	70	3.0	2.1	1.6
4.0	18.5	15.5	9.0	6.8	65	2.2	1.9	1.5
4.5	16.5	14.3	9.0	6.8	60	1.6	1.4	1.3
5.0	15.0	13.2	9.0	6.8	55	1.15	1.05	1.0
5.5	12.5	12.1	9.0	6.8	50	0.9	0.8	0.75
6.0	10.6	10.2	9.0	6.8	45	0.65	0.6	0.55
6.5	9.0	8.75	8.5	6.8	40	0.45	0.4	
7.0		7.6	8.0	6.8				
8.0		5.85	6.45	6.15				
9.0		4.7	5.2	5.5				
10.0		3.85	4.3	4.55				
11.0		3.2	3.6	3.9				
12.0		2.6	3.05	3.3				
13.0			2.6	2.8				
14.0			2.2	2.4				
15.0			1.9	2.1				
16.0			1.6	1.8				
17.0			1.4	1.55				
18.0			1.2	1.4				
19.0				1.2				
20.0				1.05				
22.0				0.75				
24.0				0.55				

A = Boom length  
 B = Working radius  
 C = Jib length  
 D = Jib offset  
 E = Boom angle

(iii)

Unit:ton

Outriggers minimum extended								
A B (m)	8.5m	14.6m	20.7m	26.8m	C D E (°)	7.5m		
						5°	25°	45°
2.5	20.0	16.0	9.0		82	3.0	2.1	1.6
3.0	20.0	16.0	9.0		75	3.0	2.1	1.6
3.5	18.8	16.0	9.0	6.8	73.5	3.0	2.1	1.6
4.0	14.5	13.6	9.0	6.8	72	2.65	2.1	1.6
4.5	11.5	11.1	9.0	6.8	70	2.2	1.85	1.6
5.0	9.5	9.1	9.0	6.8	65	1.4	1.25	1.1
5.5	8.0	7.7	8.15	6.8	60	0.9	0.85	0.75
6.0	6.9	6.55	7.05	6.8	55	0.55	0.55	0.5
6.5	6.0	5.7	6.2	6.3				
7.0		5.0	5.4	5.7				
8.0		3.8	4.3	4.5				
9.0		3.0	3.45	3.7				
10.0		2.4	2.85	3.05				
11.0		1.9	2.35	2.55				
12.0		1.5	1.9	2.15				
13.0			1.6	1.8				
14.0			1.35	1.5				
15.0			1.1	1.25				
16.0			0.9	1.05				
17.0			0.7	0.9				
18.0			0.55	0.75				
19.0				0.6				

A = Boom length  
 B = Working radius  
 C = Jib length  
 D = Jib offset  
 E = Boom angle

**PRECAUTIONS TO BE TAKEN WHEN THE OUTRIGGERS ARE EXTENDED:**

1. The total rated loads shown are for the case when the outriggers are set horizontally on firm ground. The values above the bold lines are based on the crane strength while those below are based on the crane stability.
2. The weights of the slings and hooks (main winch hook: 220kg, auxiliary winch hook: 60kg) are included in the total rated loads shown.
3. The total rated load is based on the actual working radius including the deflection of the boom.
4. The chart below shows the standard number of part lines for each boom length. The load per line should not exceed 2.9t for the main winch and 3.0t for the auxiliary winch.

<b>A</b>	8.5m	14.6m	20.7m	26.8m	<b>J</b>
<b>H</b>	7	6	4	4	1

A = Boom length    H = No. of part-line    J = Jib / Single top

5. As a rule, free-fall operation should be performed only when lowering the hook alone. If a hoisted load must be lowered by free-fall operation, the load must be kept below 1/5th of the total rated load and sudden braking operations must be avoided.
6. The total rated load for the single top shall be the value obtained by subtracting 160kg from the total rated load of the boom and must not exceed 3.0t.

## (2) Without outriggers

Unit:ton

B ( m )	Stationary						Creep (travelling at 1.6km/h or less)					
	8.5m BOOM		14.6m BOOM		20.7m BOOM		8.5m BOOM		14.6m BOOM		20.7m BOOM	
	F	G	F	G	F	G	F	G	F	G	F	G
3.0	12.2	8.2	8.7	7.2			8.5	6.5	6.7	5.0		
3.5	10.7	7.2	8.7	7.0	6.2	4.5	8.3	5.6	6.7	5.0	5.2	3.7
4.0	10.2	6.0	8.7	5.6	6.2	4.5	7.5	4.7	6.7	4.6	5.2	3.7
4.5	9.1	4.9	8.0	4.5	6.2	4.5	6.8	3.7	6.3	3.7	5.2	3.7
5.0	8.0	4.0	7.2	3.75	6.2	4.1	6.1	3.1	5.8	3.0	5.2	3.3
5.5	6.9	3.4	6.4	3.2	5.7	3.5	5.4	2.6	5.2	2.5	4.8	2.8
6.0	6.1	2.8	5.65	2.7	5.3	3.05	4.9	2.2	4.6	2.15	4.4	2.4
6.5	5.2	2.4	4.9	2.3	4.85	2.65	4.2	1.8	4.05	1.8	4.0	2.1
7.0			4.35	1.95	4.5	2.3			3.6	1.5	3.7	1.8
8.0			3.35	1.35	3.75	1.75			2.8	1.0	3.1	1.3
9.0			2.6	0.95	3.0	1.3			2.2	0.6	2.5	1.0
10.0			2.05	0.6	2.5	0.95			1.75		2.05	0.7
11.0			1.65		2.05	0.7			1.4		1.7	
12.0			1.3		1.7				1.1		1.4	
13.0					1.4						1.15	
14.0					1.15						0.95	
15.0					0.95						0.75	
16.0					0.75						0.6	
17.0					0.6							

B = Working radius F = Front G = 360°




**PRECAUTIONS TO BE TAKEN WHEN THE OUTRIGGERS ARE NOT MOUNTED:**

1. The total rated loads shown are for the case when the crane is set horizontally on firm ground. The values above the bold lines are based on the crane strength while those below are based on the crane stability. The foundation, working conditions, etc. should be taken into consideration adequately when using the crane for actual work. (Tire air pressure: 9.0kg/cm<sup>2</sup>).
2. The weights of the slings and hooks are included in the total rated loads shown.
3. The total rated loads are based on the actual working radii into which are included the deflections of the boom and the tires.
4. The chart below shows the standard number of part lines for each boom length. The load per line should not exceed 2.9t (main winch hook).

<b>A</b>	<b>8.5m</b>	<b>14.6m</b>	<b>20.7m</b>
<b>H</b>	<b>7</b>	<b>6</b>	<b>4</b>


A = Boom length  
H = No. of part-line

5. The total rated load for the single top shall be the value obtained by subtracting 120kg from the total rated load of the boom and must not exceed 3.0t.
6. Free-fall operations should not be performed without outriggers.
7. The 26.8m boom, the jib and the single top should not be used without the outriggers.
8. The boom must be kept inside a 2° area (1° each to the left and right) over front of the carrier when performing "Over front" crane operations without the outriggers.



9. When creeping while hoisting a load, the swing brake should be applied, the load should be kept as close to the ground as possible but not touching the ground and the speed should be kept at 1.6km/h or less. In particular, any abrupt steering, starting or braking must be avoided.
10. Crane operations should not be performed when creeping while hoisting a load.


## WORKING RADIUS - LIFTING HEIGHT



**NOTES:**

1. The deflection of the boom is not incorporated in the figure above.
2. The figure above is for the case when the outriggers are fully extended (360°).

**DIMENSIONS** (1/100)



◆ MEMO ◆

A series of horizontal dashed lines for writing.